

Terminal Tractor/Yard Spotter

Used Yard Spotter Northwest Territories - Tow tractors are a common piece of industrial equipment used in large buildings, arenas, warehouses, airports and manufacturing plants for moving loads horizontally. They go by different names including tow tugs and towing tractors. They are capable of towing several trailers in a train formation. Some are designed specifically to tow large aircraft in order to position them into and out of airport terminals and hangars. Tractive effort is how these machines transport loads. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. The heavier the load is, the more tractive effort is needed. Based on this principle, the tow tractor works by lifting a part of the load it is towing while making sure the load's wheels remain on the ground. The load is partially lifted by use of the tow tractor's hydraulic mast which is specifically designed to produce downforce on the drive wheel immediately beneath it, increasing the tractive effort. The tow tractor is capable of transporting very heavy and large loads thanks to the traction it provides.

Types of Tow Tractors Two types of towing tractors include heavy-duty tow tractors and load carriers.

Load Carriers Many industries including airport baggage divisions, manufacturing, parcel transportation and e-commerce rely on moving items of various sizes to and from different locations. Load carrier tow tractors or tow tugs are especially useful for these types of applications because they allow the single items to be gathered and stacked on the wheeled platforms, ready to be attached for tow and transport by the tow tractor. These load carrier tow tractors fall under the material handling equipment industry which includes other machines such as pallet jacks, forklifts and cranes. These units only transport loads at ground level and do not lift or lower items from shelving or off the ground. This means that the load has already been on wheels or placed on a wheeled platform before transport. The wheeled platforms are called bogies, trollies or skates. The tow tractor attaches to the trolley and operates similarly to how train cars are attached to a locomotive. Generally, the steel coupling on the tow tug's male-end joins to the front trolley's female-end. The trolley's back portion has a male-end steel coupling that can be used to connect a variety of trollies to a single tug. Tow tractors are capable of moving many machines in a variety of conditions. Different trolley types are on the market to facilitate better transportation customization. Many trollies can be connected since they are compatible with one another. Since multiple trolley types can be utilized in a single train, there is flexibility. Load carrier tow tractors deliver a clear view for the operator which can be better than relying on forklifts. Further, load carrier tow tractors tow their trollies behind them in a forward-only direction which decreases the safety concerns created by forklifts operating in reverse. These safety considerations are of special importance in busy areas such as manufacturing floors and airports. Towing solutions are a good alternative to traditional forklifts to handle many single items. Tugs are easy to move and safe to use. The operator doesn't require a license, which is another benefit compared to forklifts. This is because the load is not lifted from the ground so it does not fall under the usual restrictions and licensing required of standard forklifts, cranes and other load lifting equipment. There are three kinds of load carrier tow tractor units to choose from; pedestrian, stand-in and rider-seated.

Pedestrian Tow Tractors Pedestrian tow tractors go by many names including electric tow tractor, electric tug, or electric tugger. These units are walk-behind models that move wheeled loads. It is compact, maneuverable and easy to use.

Stand-in Tow Tractors The most common design for businesses that rely on horizontal manufacturing transport and order picking are stand-in tow tractors. These units deliver a secure driver platform and deliver a smaller footprint compared to the rider-seated models.

Rider-Seated Tow Tractors Similar to stand-in tow tractors, rider-seated units have a seated operator platform. Rider-seated models are used for moving loads longer distances. They are popular for airport luggage transport to move checked baggage from the check-in counter to the aircraft parked at the terminal. Reducing rider fatigue, the rider-seated models deliver more efficiency.

Heavy Duty Tow Tractors The pushback concept is commonly used in aviation for cargo and large passenger planes. Pushback refers to the process of pushing an aircraft back

from an airport terminal by some means other than the aircraft's own power. This pushback process is done by using specially designed heavy duty tow tractors called pushback tractors or pushback tugs. Pushback tractors are built with a low-profile to allow them to move underneath the nose of the aircraft so that it can attach. Since the aircraft weight is heavy, these units need to be heavy in order to retain adequate ground friction to move the aircraft. A typical tractor for large aircraft weighs up to 54 tons. They usually have a driver's cab that can be raised and lowered to increase visibility when reversing. While the vehicle is referred to as a pushback tug or pushback tow tractor, it is also used to tow aircraft in areas where taxiing the aircraft is not practical or safe, such as moving large aircraft in and out of maintenance hangars. There are two subtypes of pushback tow tractors: 1. Conventional; and 2. Towbarless. Conventional Pushback Tow Tractors Conventional tugs use a tow bar to connect the tug to the nose landing gear of the aircraft. The tow bar is fixed laterally at the nose landing gear, but may move slightly vertically for height adjustment. At the end that attaches to the tug, the tow bar may pivot freely laterally and vertically. Acting like a giant lever, the tow bar can rotate the nose landing gear. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. Heavy-duty towbars required for sizeable aircraft ride on their own wheels when they are disconnected from the machine. The hydraulic jacking mechanism is attached to the wheels, allowing the towbar to lift to the correct height in order to mate with the tug and the aircraft. The same means are used in reverse during the pushback process to raise the towbar wheels from the ground. The towbar is capable of being connected at the tractor's rear or front, depending on if the machine needs to be pulled or pushed. Depending on whether the aircraft needs to be pushed or pulled, the towbar can be attached to the front or rear of the tractor. Towbarless Pushback Tow Tractors Towbarless tractors do not use a towbar; they scoop up the nose landing gear and lift it off the ground, allowing the tug to maneuver the aircraft. This offers better control and higher speeds while eliminating the requirement of having a worker stationed in the cockpit to put the brakes on. Simplicity is the main advantage of the towbarless tugs since it is not necessary to maintain a variety of towbars. Directly connecting the tug to the landing gear allows operators to have better responsiveness and control while moving the aircraft.